



quality.

→ Simply by Touch

The philosophy "power on and working" is the first priority for ProdUser®

In fact, without needing to deal with an operating system and/or peripheral units the control interface (GUI) is very simple to understand – and easy to use, even for technically unskilled users, because all inputs may be given by a stylus or simple touch of the screen.



→ Broadcast Quality equalling Professional Studios



Regardless what device or system you desire to connect, ProdUser® recognizes them all and chooses the optimal recording quality automatically.

You can connect a digital camera, a camcorder (old or new, analog or digital), a video recorder, a broadcast, monitoring or operating room camera: ProdUser® offers you all of these options.

You can record data, pictures or entire presentations directly from a CD-ROM, a memory card or by the integrated network adaptor (LAN). Simply ingenious.

→ ProdUser® – the Multimedia Specialist Features:

• Professional Video Editing

Professional video editing system allows you to compose live or recorded video in an ingeniously easy way — with storyboard technology. With the twist of the wrist you can mix video clips, photos and pictures to a marvellous multimedia presentation.

• DVD Recorder and Player

ProdUser® saves data quickly with a touch of the screen and without additional devices on a CD-ROM or DVD or records them on a videotape.



Simply ingenious.

PPF[™] (Picture Paint Function)

With PPF[™] you can make interactive presentations: paint directly on the running picture or video – with a stylus or by finger pressure – to add explanations or highlight important information.



• Real-time Editing

All features are in real-time: PPF™, transition effects, colour corrections etc. All your changes are visible on the integrated monitor or on the connected television or beamer projection at the same time.



PRODUSER PRODUSER

Compatibility

ProdUser® offers innumerable possibilities: it allows working with any current format. The automatic conversion of PowerPoint® presentations or pictures in DICOM® format into high quality video format is outstanding and unique.

ProdUser® unites all of these formats. Without PC or PC-based software it is possible to record projects on DVD-R/-RW or DVD+R/+RW.

Archive

ProdUser® is a solution to the challenge of archiving projects and data because they can be archived on a DVD, CD-ROM or on a second (removable) hard drive. For transferring or saving the data to other systems, you can use the integrated LAN adaptor.

→ Obsolescence-proof

Your investment into ProdUser® is obsolescence-proof: thanks to the modular set-up of the hardware and software developed by Rigoletto Technologies, updates and add-ons can be integrated to ProdUser® easily and cost effectively.

Ingeniously simple.

→ Functions and features

12,1" TFT touch-screen display as working- and control panel

Second 12,1" TFT display as presentation screen

Audio/video recording on removable hard drive

Audio/video recording on DVD, CD-ROM (-R, -RW, +R, +RW)

Audio/video playback from HDD, DVD or CD-ROM

Realtime video- and picture editing

PPF™ (Picture Paint Function)

Import of JPG, PNG, BMG, GIF, MNG, PGM, PPM, XBM, XP, DICOM® and PowerPoint® files

Network adaptor (LAN) for internet access or transfer of live pictures via IP

→ Technical data

Inputs

1 x Analog Video Composit

1 x Scart Composit

2 x Analog S-Video (Y/C)

1 x Microphone 3,5 mm

2 x XLR-Microphone (L/R)

2 x XLR-LINE (L/R)

1 x Optical S/P-DIF

1 x Mini-DV (4 pin), DV25 (IEEE 1394)

1 x DV (6 pin), DV25 (IEEE 1394)

1 x Coax. AES/EBU

Outputs

2 x Analog Video Composit

1 x Scart Composit

2 x Analog S-Video (Y/C)

2 x XLR-LINE (L/R)

1 x Optical S/P-DIF

1 x Mini-DV (4 pin), DV25 (IEEE 1394)

1 x DV (6 pin), DV25 (IEEE 1394)

1 x Coax. AES/EBU

1 x Analog RGB (YUV)

1 x Headphone Output Stereo 3,5 mm

1 x SVGA (800 x 600) (DVI-I)

Digital connectors

4 x USB Interface

1 x RS 232 Interface

1 x RS 422 Interface

1 x LANC

1 x LTC

GPI-Interface

10/100 Mb/s Ethernet LAN

Other features

D1 Resolution, 25/30 FPS (4:2:0/4:2:2)

 $Encoding/Decoding: \quad MPEG~2~(I-Frame~only)$

(up to 25 Mb/s) $4\!:\!2\!:\!0$

(up to 50 Mb/s) 4:2:2

DVD

Encoding/Decoding: MPEG 2 (IBP)

(up to 15 Mb/s) 4:2:0

Additional features

- · 1 x SDI (BNC/270 Mb/s)
- · Streaming RTP / UDP, Multicast/Unicast up to 50 Mb/s VBR, CBR
- · DVB-T/C/S Input
- · MPEG4 Encoder / Decoder up to 25 Mb/s
- · Videoconferencing
- · H263, H264 Encoder / Decoder
- · MP@ML, SP@ML, MPEG4, SOP@level3, ASP@level5

DICOM is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information.

PowerPoint is a registered trademark of Microsoft Corporation in the United States and/or other countries.



© 2004 Rigoletto Technologies AO. All rights reserved. Technical specifications are subject to change for product improvements without prior notice.